








U-Coat Protective Coatings June 2026



U-SHIELD Coating Powder, approved for Flame Spray - heat applied for Coating on Various Surfaces such as Steel, Aluminum, Concrete, Fiberglass, Wood and other U-V stable, high flexibility, soft grip, durable coating, chemical inert, salt resistant, easy repair self healing, Drinking Water certified, various color options available:

1)	U-SHIELD Pro17 TOUGH COAT for Heavy Duty Industrial Applications
	U-S17900550-BL: U-SHIELD Pro17 BLACK 9005 FS (50)
	U-S17500550-BB: U-SHIELD Pro17 BRIGHT BLUE 5005 FS (50)
	U-S17501150-DB: U-SHIELD Pro17 DARK BLUE 75011 FS (50)
	U-S17300950-RBR: U-SHIELD Pro17 RUST BROWN 3009 FS (50)
	U-S17801750-DBR: U-SHIELD Pro17 DARK BROWN 8017 FS (50)
	U-S17600550-DG: U-SHIELD Pro17 DARK GREEN 6005 FS (50)
	U-S17704250-MG: U-SHIELD Pro17 MEDIUM GREY 7042 FS (50)
	U-S17704350-DG: U-SHIELD Pro17 DARK GREY 7043 FS (50)
	U-S1710550-TO: U-SHIELD Pro17 TRAFFIC ORANGE 105 FS (50)
	U-S17300150-R: U-SHIELD Pro17 RED 3001 FS (50)
	U-S17901650-WT: U-SHIELD Pro17 WHITE 9016 FS (50)
	U-S17101850-TY: U-SHIELD Pro17 TRAFFIC YELLOW 1018 FS (50)
	SPECIALTY COLORS ON REQUEST ONLY:
	U-S17CLS70-CL: U-SHIELD Pro17 CLEAR FS (70)
	U-S17125750-BT: U-SHIELD Pro17 BEIGE TAN 1257 FS (50)
	U-S17101350-OWT: U-SHIELD Pro17 OYSTER WHITE 1013 FS (50)
	U-S17710750-PU: U-SHIELD Pro17 PURPLE 7107 FS (50)
	U-S1712850-T: U-SHIELD Pro17 TURQUOISE 128 FS (50)
	U-S17200950-SO: U-SHIELD Pro17 FEDERAL SAFETY ORANGE 2009 FS (50)
	U-S171365550-SY: U-SHIELD Pro17 FEDERAL SAFETY YELLOW 13655 FS (50)
2)	U-SHIELD PA Semi-Flex Coating for everyday Applications
	U-SPA536-ABL: U-SHIELD PA AQUA BLUE 536 RAL 5017
	U-SPA700-BL: U-SHIELD PA BLACK 700 RAL 9005
	U-SPA475-GR: U-SHIELD PA GREEN 475 RAL 6005
	U-SPA613-LG: U-SHIELD PA LIGHT GREY 613 RAL 7035
	U-SPA233-R: U-SHIELD PA RED 233 RAL 3020
	U-SPA110-W: U-SHIELD PA WHITE 110 RAL 9016
	U-SPA344-YW: U-SHIELD PA YELLOW 344 RAL 1021

3)	U-SHIELD POLYFUSION Flexible Membrane for sealing Concrete and more
	U-SPFM-AG: U-SHIELD PFM ASH GREY
	U-SPFM-BL: U-SHIELD PFM BLACK LIME
	U-SPFM-CB: U-SHIELD PFM CARIBBEAN BLUE
	U-SPFM-EB: U-SHIELD PFM EGYPTIAN BLUE
	U-SPFM-NB: U-SHIELD PFM NAVY BLACK
	U-SPFM-PG: U-SHIELD PFM PERSIAN GREEN
	U-SPFM-SMWHT: U-SHIELD PFM SMOKEY WHITE
RECOMMENDED in combo with Epoxy Resin 503 and 505	
Polyres 503	U-503 RES Liquid Epoxy Standard Cure. A two component, solvent free, low viscosity Epoxy primer. Cures at low temperatures. Designed to seal porous, dry surfaces. 4 l = 12.5 lbs./kit Improves adhesion of top coats
Polyres 505	U-505 EDS Liquid Epoxy Quick Cure. A two component, solvent free, low viscosity Epoxy primer. Cures at low temperatures. Designed for green or wet concrete surfaces. 4 l (12.5 lbs) Improves adhesion of top coats.

U-Coat Technologies, Inc. - 2075 Lake Avenue SE - Largo, FL 33771 - 727-322-4005 - sales@u-coat.com